

CODE: MBK22-LITHIUM-HGEL-2

ERP: 0501160

## Portable Fire Extinguisher 2Lt for Lithium Batteries Portable

Fire Extinguisher 2Lt Hydrogel, with One Seam Vessel with INTERNAL PLASTIC LAYER and External Thread, Pressure Gauge Safety Release Valve and Gauge Non Return Valve. Appropriate for use at Lithium Ion Battery Fires.

Metallic Bracket Included



### CHARACTERISTICS

Approval Type	BENOR
Extinguisher Type	Portable
Pressure Type	Stored Pressure
Suppression Agent Type	Agent for Li-on Batteries
Capacity	2
Fire Rating	5A 5F
Extinguishing Agent	HydroGel BM 048
Operating Temperature	+5 ~ +60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	3,2 L
Cylinder Height	304±2 mm
Cylinder Diameter	130±2 mm
Cylinder Neck Thread	M45X1,5
Valve Material	AA6061 (anodized)
Cylinder Material	DC04/DC03
Safety Valve	22~27 bar
Approx. gross Weight	~4,0 kg
Approx. Dimensions	395x130 mm
Paint Finish	RAL3000



BENOR



Issue Date: 23/05/2024

Information may change

**HEADQUARTERS:** KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

**ATHENS DISTRIBUTION CENTER:** SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

**NORTH GREECE DISTRIBUTION CENTER:** 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

**CENTRAL & EAST CRETE DISTRIBUTION CENTER:** P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

[www.mobiakfire.com](http://www.mobiakfire.com)